



# SST-750

## Concentrated Bio-Formulation for Waste Degradation & Odor Control in Drain Lines And Grease Traps

### Product Information Sheet

#### Product Description

SST-750 is designed to improve and accelerate the digestion of grease and organic compounds that build up and cause odors in waste water systems. SST-750 is formulated with billions of friendly microorganisms, enzyme systems and nutrients that demonstrate superior activity. SST-750 is safe for the environment, plumbing, pipes, and wastewater systems. It contains no harsh chemicals, solvents, or hazardous compounds.

#### Product Specifications

**Bacteria Type:** A blend of non-pathogenic Bacillus spores and vegetative strains.

**Bacterial Count:** 2 Billion C.F.U./gm

**Effective pH range:** 4.5-8.5

**Effective temperature range:** 50° F-145° F

**Appearance/Odor:** Tan powder/earthy

**Shelf life:** 1 year at 35-95 degrees F.

*Store in cool dry place.*

#### Product Application

Application for Grease Traps: 200 gallon- ½ pound per day. 500-1500 gallons-1 pound per day. 1500 gallon and larger- 2 pounds per day.

Application for Drain lines: Mix ½ -1 pound with 2 gallons of water and apply weekly during low flow times.

#### **Comments:**

Read MSDS before using. Avoid inhalation of dust. Wash hand thoroughly after handling. Avoid contact with eyes and skin.